

S-52

METAPACE S-52

2D imager at a great price

Technical specifications

PROPERTIES

Type	2D imager
Light source	Illumination: white LED Aiming: red LED, 617 nm
Movement tolerance	40 – 200 mm, EAN/UPC
Print contrast	Min. 25% reflectance difference
Scanning angle	Rotation: $\pm 55^\circ$; pitch: $\pm 65^\circ$; skew: $\pm 30^\circ$
Supported barcodes	QR Code, Data Matrix, PDF417, AZTEC, CODE128, EAN-8, EAN-13, UPC-E, UPC-A, Interleaved 2 of 5, ITF14, MATRIX 25, Code 39, UCC/ EAN-128, Code 11, ISBN, INDUS- TRIAL25, STANDARD25, Plessey, MSI_Plessey

ELECTRONICS

Voltage	5 V \pm 10% @ 170 mA
---------	------------------------

INTERFACE

I/F ports	USB
-----------	-----

SPECIFICS

Impact resistance	Resists multiple 1.5 m drops to concrete
-------------------	---

ENVIRONMENT

Operating temperature	-20°C – 60°C
Storage temperature	-40°C – 70°C
Humidity	5% – 95% RH

HOUSING

Dimensions (W x H x D)	70 x 94 x 173 mm
Weight	220 g (incl. cable)
Colour	Black

WARRANTY

Period	24 months
--------	-----------

Highlights

- + Reads all common 1D and 2D barcodes
- + Ergonomic design, user-friendly handling
- + Easy setup via plug & play
- + Blue LED and acoustic signal for quick feedback



UNPACK AND
GET STARTED