# CITIZEN

## Fast, powerful POS printing

Fast retail top-exit

### CT-S601IIR

# POS, Receipt printer (thermal 3 inch / 80mm)

#### Applications

- Hospitality
- Journal
- Kitchen
- Retail



### The upgraded CT-S601IIR

A new and special version of the popular CT-S601II printer, the new CT-S601IIR arrives as a Re-Stick Liner-Free Model that prints top exit, self-adhesive labels and has been designed to serve across multiple applications.

# Eco-friendly POS printing solutions

Producing cost-effective, continuous roll label output, the CT-S601IIR also highlights mark-leading eco-friendly capabilities. Offering users significant waste reduction, the new printer produces entirely Liner-Free labels and is compatible with MAXStick® media. Also, due to its ability to adjust the print length to suit the required content, CT-S601IIR reduces waste further still.

### Internal power supply

All 80mm POS printers from Citizen offer an internal power supply.



Available in either sleek black or classic ivory

## TOMORROW'S PRINTING TODAY

Citizen Systems Europe GmbH, Elizabeth House, 56-60 London Road, Staines-Upon-Thames, TW18 4HF, United Kingdom

# CITIZEN



Supported by an adaptable range of optional interfaces including USB, LAN, WiFi, Bluetooth and others.

### **Specifications**

Model	CT-S601IIR
Printing Technology	Direct Thermal
Resolution	203 dpi
Print Speed (maximum)	175mm/sec
Print Width (maximum)	45 / 48 / 52 / 54 / 64 / 68 / 72 / 80 mm
Media Width (min to max)	58 / 60 / 80 / 83 mm (+/- 1mm)
Roll Size (max), Core Size	83 mm outside diameter
Media Thickness (min to max)	65µm to 90µm
Media Sensor	Paper end
Main Interface	None: interface card slot for optional card
Interface	Parallel (IEEE 1284 compliant), Serial (RS-232C compliant), USB, Premium Wireless LAN, Ethernet (SEH), Bluetooth with Apple <sup>™</sup> MFi compatibility, Compact Wireless LAN, Ethernet, Ethernet + USB host, USB 2.0, Powered USB
Power supply	100 – 240V, 50-60 Hz, external power supply (supplied) or 24V DC
Reliability	100 million pulses, 75km
Control panel	Feed button, 3 LEDs
Emulations (Languages)	ESC/POS™
Drivers and software	Free-of-charge from website, including support for various platforms

### CT-S601IIR

## POS, Receipt printer (thermal 3 inch / 80mm)

### **Features & Benefits**

- Low space requirement integrated power supply enables clean work station
- Mobile-POS ready
- Easy notification built-in buzzer
- ENERGY STAR® compliant
- Small footprint
- Recyclable packacking
- Tool-free maintenance



Producing super-fast, Liner-Free labels up to 83 mm wide, at a speed of 175 mm per second and at 203 dpi

### CITIZEN SYSTEMS EUROPE GMBH

# CITIZEN

Model	CT-S601IIR
Size (W x D x H) and Weight	145x192x148 mm, 2 Kg, DC version 145x192x120, 1.6 Kg
Cutter	Guillotine type, partial
EMC and safety standards	CE, UL, TUV, C-UL, FCC class A, VCCI

All product names are trademarks of the respective manufacturers. Zebra®, ZPL and EPL are trademarks of ZIH Corp. Datamax® is a trademark of Datamax-O'Neil Corporation. Designs, specifications and availability are subject to change without notice. Errors and omissions excluded. © Citizen Systems Europe GmbH, V.1.0

### CT-S601IIR

POS, Receipt printer (thermal 3 inch / 80mm)