



K120 FULLY RUGGED TABLET

- 8th Generation Intel[®] Core[™] i7 / i5 Processor
- 12.5" FHD LumiBond[®] 2.0 Display with Getac Sunlight Readable Technology (1,200 nits) and Capacitive Touchscreen
- Enhanced Enterprise Security with optional Intel vPro, Windows Hello face-authentication camera, and multi-factor authentication options
- Multi-mode usage streamlined by extensive accessory selections
- LifeSupport[™] Battery Swappable Technology



e

Dro

Rugged Mobile Computing Solutions

Specifications

Generation

Operating System Windows 10 Pro

Mobile Computing Platform

Intel® Core™ i5-8250U Processor 1.6GHz Max. 3.4GHz with Intel® Turbo Boost Technology - 6MB Intel® Smart Cache

- 6MB Intel® Smart Cache Platform Options: Intel® Core[™] i5-8350U vPro[™] Processor 1.7GHz Max. 3.6GHz with Intel® Turbo Boost Technology - 6MB Intel® Smart Cache Intel® Core[™] i7-8550U Processor 1.8GHz Max. 4.0GHz with Intel® Turbo Boost Technology - 8MB Intel® Smart Cache Intel® Core[™] i7-8650U vPro[™] Processor 1.9GHz Max. 4.2GHz with Intel® Turbo Boost Technology - 8MB Intel® Smart Cache VGA Controllor

VGA Controller Intel® UHD Graphics

Display 12.5" IPS TFT LCD FHD (1920 x 1080) Protection film 1200 nits LumiBond[®] display with Getac sunlight readable Capacitive multi-touch screen

Storage & Memory

4GB DDR4 Optional: 8GB / 16GB / 32GB DDR4 256GB SATA SSD Optional: 512GB / 1TB SATA SSD Optional: 256GB / 512GB / 1TB PCIe NVMe SSD

Keyboard

Power button 5 tablet programmable buttons

Pointing Device

- Touchscreen Capacitive multi-touch screen Optional: Dual mode touchscreen (multi-touch and digitizer)

Expansion Slot

Optional: 1D / 2D imager barcode reader Optional: Serial port (9-pin; D-sub), or USB 2.0 port I/O Interface

To Interface Tablet: FHD webcam x 1^x 8M pixels auto focus rear camera x 1 Headphone out / mic-in combo x 1 DC in Jack x 1 USB 3.2 Gen 1 Type-A x 1 USB 3.2 Gen 1 Type C x 1 LAN (RI45) x 1 HDMI x 1

LAN (KI45) x 1 HDMI x 1 Docking connector x 2 Optional: Windows Hello face-authentication camera (front-facing) x 1^x Optional: RF antenna pass-through for GPS, WLAN and WWAN

- Optional Keyboard Dock:

Optional Keyboard Dock: DC in Jack x 1 USB 3.2 Gen 1 x 3 LAN (RV45) x 1 HDMI x 1 VGA x 1 Serial port (9-pin; D-sub) x 1 RF antenna pass-through for GPS, WLAN and WWAN

Communication Interface

10/10/1000 base-T Ethernet Intel® Dual Band Wireless-AC 8265, 802.11ac Bluetooth (v4.2) Optional: Dedicated GPS Optional: 4G LTE mobile broadband

Security Feature

TPM 2.0

Privizional: Intel® vPro™ Technology Optional: Intel® vPro™ Technology Optional: Smart Card reader or HF RFID reader^{a, iii} or fingerprint reader^a

Power

AC adapter (65W, 100-240VAC, 50 / 60Hz) Li-lon smart battery (11.1V, typical 2100mAh; min. 2040mAh) x 2 LifeSupport[™] battery swappable technology Optional: High capacity battery (14.4V, typical 3450mAh; min. 3300mAh) x 2

Dimension (W x D x H) & Weight

Tablet: 329.5 x 238 x 24 mm (12.97" x 9.37" x 0.94") 1.8 Kg (3.96 lbs)^v Tablet+Optional Keyboard Dock: 340.5 x 307.5 x 47 mm (13.40" x 12.10" x 1.85") 3.25 Kg (7.16 lbs)^v

Rugged Feature MIL-STD-810G certified

Environmental Specification Temperature

Operating: -29°C to 63°C / -20°F to 145°F Storage: -51°C to 71°C / -60°F to 160°F

Humidity: - 95% RH , non-condensing

Pre-installed Software

Getac Utility Getac Camera Getac Geolocation Getac Barcode Manager^{si} Optional: Absolute Persistence®

Accessories Battery (11.1V, typical 2100mAh; min. 2040mAh) AC Adapter (65W, 100-240VAC) Capacitive Stylus

Optional:

Carry Bag Battery (11.1V, typical 2100mAh; min. 2040mAh) High Capacity Battery (14.4V, typical 3450mAh; min. 3300mAh) Milti-bay Charger (Dual Bay) Multi-bay Charger (Eight-Bay) AC Adapter (65W, 100-240VAC) Office Dock AC Adapter (120W, 100-240VAC) MIL-STD-461 Certified AC Adapter (90W, 115-230VAC) Vehicle Adapter (120W, 11-22) (DC) Vehicle Adapter (120W, 11-32VDC) Digitizer Pen Capacitive Stylus Protection Film Tablet Hard Handle Hand Strap Shoulder Strap (2-point) Shoulder Harness (4-point; handsfree) Keyboard Dock

Vehicle Dock Office Dock

Spare SSD Kit Bumper-to-Bumper Warranty

Accidents can take your equipment out of service when you least expect it, especially in a rugged environment, which can cause costly equipment downtime

That is why Getac has introduced accidental damage as standard under our Bumper-to-Bumper warranty, to help minimize your enterprise IT costs. Bumper-to-Bumper is your hassle-free guarantee. That means you can depend on us to have your unit back in service within days. Standard

3 years Bumper-to-Bumper

- Bluetooth performance and connectable distance may be subject to interference with the environments and performance on client devices, users may be able to reduce effects of interference by minimizing the number of active Bluetooth wireless devices that is operating in the area. 13.56MHz Contactless HF RFID / NFC reader (ISO 15693, 14443 AVB, Mifare and FeliCaTM compliant)
- compliant). LF/HF RFID reader option is not Energy Star 8.0 compliant. Smart card reader, HF RFID reader and
- Smart card reader, HF RHD reader and fingerprint scanner are mutually exclusive options.
 Weight and dimensions vary from configurations and optional accessories; optional high capacity batteries add approx. 11 mm (H), 0.20 kg.
 MIL-STD-461G 90W AC adapter sold separately.
 Available with limited configurations.
 Torop test results vary from configurations and optional accessories

- VIII Drop test results vary from configurations and optional accessories.
 ix Tested by a national independent third party test lab following MIL-STD-810G.
 x FHD webcam and optional Windows Hello face-authentication camera (front-facing) are mutually exclusive options.
 xi Available when barcode reader option is selected.

K120 Fully Rugged **Tablet**



Docking Solutions

	Vehicle Dock for Tablet Mode	Vehicle Dock for Laptop Mode	Office Dock for Tablet Mode	Office Dock for Laptop Mode
Serial Port	1	1	1	1
VGA	1	1	1	1
Microphone			1	1
Audio Output			1	1
DC in Jack	1	1	1	1
USB	USB 2.0 x 3 USB 3.2 Gen1 x 3	USB 2.0 x 3 USB 3.2 Gen1 x 3	USB 2.0 x 2 USB 3.2 Gen1 x 3	USB 2.0 x 2 USB 3.2 Gen1 x 3
LAN	2	2	2	2
HDMI	1	1	1	1
RF Antenna Connector	3 (WWAN, WLAN, GPS)	3 (WWAN, WLAN, GPS)		
Kensington Lock	1	1	1	1



Getac (UK) Ltd.

Getac House, Stafford Park 12, Telford, Shropshire TF3 3BJ, United Kingdom Tel : +44 (0) 1952 207 222 Sales-Getac-UK@getac.com | www.getac.com/en/



Copyright © 2021 Getac Technology Corporation and/or any of its affiliates. All Rights Reserved ation provided herewith is for reference only available specification shall be subjected to quotation by request. V01M02Y21UK





K12O-EX FULLY RUGGED TABLET

- ATEX / IECEx Zone 2 / 22 Certified for hazardous locations
- 8th Generation Intel[®] Core[™] i7 / i5 Processor
- 12.5" FHD LumiBond[®] 2.0 Display with Getac Sunlight Readable Technology (1,200 nits) and Capacitive Touchscreen
- Enhanced Enterprise Security with optional Intel vPro, Windows Hello face-authentication camera and multi-factor authentication options





Rugged Mobile Computing Solutions

Specifications

Generation

Operating System Windows 10 Pro

Mobile Computing Platform

Intel® Core[™] i5-8250U Processor 1.6GHz Max. 3.4GHz with Intel® Turbo Boost Technology - 6MB Intel® Smart Cache

Platform Options: Intel® Core™ i5-8350U vPro™ Processor 1.7GHz Max, 3.6GHz with Intel® Turbo Boost Technology - 6MB Intel[®] Smart Cache

Intel® Core[®] i7-8550U Processor 1.8GHz Max. 4.0GHz with Intel® Turbo Boost Technology - 8MB Intel® Smart Cache Intel[®] Core[™] i7-8650U vPro[™] Processor 1.9GHz

Max. 4.2GHz with Intel® Turbo Boost Technology - 8MB Intel[®] Smart Cache

VGA Controller Intel® UHD Graphics

Display

12.5" IPS TFT LCD FHD (1920 x 1080) Anti-static protection film 1200 nits LumiBond® display with Getac sunlight readable Capacitive multi-touch screen

Storage & Memory

4GB DDR4 Optional: 8GB / 16GB / 32GB DDR4 2 56GB SATA SSD Optional: 512GB / 1TB SATA SSD Optional: 256GB / 512GB / 1TB PCIe NVMe SSD

Keyboard

Power button 5 tablet programmable buttons

Pointing Device

Touchscreen

Capacitive multi-touch screen Optional: Dual mode touchscreen (multi-touch and digitizer)

Expansion Slot Optional: 1D / 2D imager barcode reader Optional: Serial port (9-pin; D-sub), or USB 2.0 port

I/O Interface

FHD webcam x 1^{vi} 8M pixels auto focus rear camera x 1 Headphone out / mic-in combo x 1 DC in Jack x 1 USB 3.2 Gen 1 Type-A x 1 USB 3.2 Gen 1 Type C x 1 LAN (RJ45) x 1 HDMI x 1

Optional: Windows Hello face-authentication camera (front-facing) x 1^{vi}

Communication Interface

10/100/1000 base-T Ethernet Intel® Dual Band Wireless-AC 8265, 802.11ac Bluetooth (v4.2)ⁱ Optional: Dedicated GPS Optional: 4G LTE mobile broadband

Security Feature TPM 2.0

Kensington Lock Optional: Intel® vPro™ Technology Optional: Smart Card reader or HF RFID reader[#]

Power

AC adapter (65W, 100-240VAC, 50 / 60Hz) Li-lon smart battery (11.1V, typical 2100mAh; min. 2040mAh) x 2

Dimension (W x D x H) & Weight

329.5 x 238 x 24 mm (12.97" x 9.37" x 0.94") 1.86 kg (4.10 lbs)ⁱⁱⁱ

Rugged Feature MIL-STD-810G certified

IP65 certified Vibration & 6 feet drop resistant^{iv, v} ATEX & IECEx certified

Environmental Specification

Temperature Operating: -21°C to 63°C / -6°F to 145°F Storage: -51°C to 71°C / -60°F to 160°F

Humidity: - 95% RH, non-condensing

Explosion Protection ATEX / IECEx Zone 2/22 Ex II 3G Ex ic op is IIC T4 Gc Ex II 3D Ex ic op is IIIB T130°C Dc

Pre-installed Software

Getac Utility Getac Camera Getac Geolocation Getac Barcode Manager^{vii} Optional: Absolute Persistence®

Accessories Battery (11.1V, typical 2100mAh; min. 2040mAh) AC Adapter (65W, 100-240VAC) Capacitive Stylus Optional: Ac Adapter (65W, 100-240VAC)

Digitizer Pen Capacitive Stylus Hand Strap Shoulder Strap (2-point) Spare SSD Kit

Bumper-to-Bumper Warranty

Accidents can take your equipment out of service when you least expect it, especially in a rugged environment, which can cause costly equipment downtime.

That is why Getac has introduced accidental damage as standard under our Bumper-to-Bumper warranty, to help minimize your enterprise IT costs. Bumper-to-Bumper is your hassle-free guarantee. That means you can depend on us to have your unit back in service within days. Standard

3 years Bumper-to-Bumper

- i Bluetooth performance and connectable distance may be subject to interference with the environments and performance on client devices, users may be able to reduce effects of interference by minimizing the number of active Bluetooth wireless devices that is operating in the area.
- Smart card reader and HF RFID reader are mutually exclusive options. Weight and dimensions vary from configurations and optional accessories. Drop test results vary from configurations and ii
- iii
- iv
- optional accessories. Tested by a national independent third party test lab following MIL-STD-810G.
- FHD webcam and optional Windows Hello face-authentication camera (front-facing) are
- wii Available when barcode reader option is selected.

K120-EX Fully Rugged **Tablet**





Getac (UK) Ltd.

Getac House, Stafford Park 12, Telford, Shropshire TF3 3BJ, United Kingdom Tel : +44 (0) 1952 207 222 Sales-Getac-UK@getac.com | www.getac.com/en/



Copyright © 2021 Getac Technology Corporation and/or any of its affiliates. All Rights Reserved tion provided herewith is for reference only available specification shall be subjected to quotation by request. V01M02Y21WW