ScanPal EDA51

Mobile Computer

Honeywell

THE POWER OF CONNECTED

Small businesses need a tool that will help their mobile workers get more done in less time – working more effectively and efficiently every day.

The ScanPal[™] EDA51 mobile computer, the newest member of Honeywell's popular ScanPal family, is that tool. With a fast Qualcomm[®] Snapdragon[™] SDM450 processor and robust wireless connectivity, your workers can access crucial business apps and information when they need it – and provide the best possible service to your customers.

Instantly capture virtually any barcode in any condition – the ScanPal EDA51 comes with a powerful Honeywell scanner. Or document everything from proof of delivery to damaged packages with its powerful 13-megapixel color camera.

With its intuitive, modern touchscreen design, the ScanPal EDA51 device is as comfortable and easy to use as a consumer smartphone, eliminating any learning curve for your workers. But it's also rugged enough to survive tough field service and retail environments.

The ScanPal EDA51 is also ready to work as hard as your workers do. The large, vivid 5-inch display allows plenty of information to be displayed for interaction with your back-office systems and your customers, while the powerful 4000 mAh lithium-ion battery lasts a full shift and beyond. The thin, lightweight design makes it easy to carry and pocket the device, and use it comfortably all day long.

Priced right for small business, the ScanPal EDA51 helps you protect your investments while reducing costs. It runs Android™ O and is technically upgradeable through Android Q, giving your business flexibility and built-in investment protection. Plus, it's backward-compatible with ScanPal EDA50 accessories, allowing you to reuse existing batteries and chargers and reduce your total cost of ownership.



The ScanPal EDA51 helps small businesses increase employee efficiency with an intuitive touchscreen, a powerful processor, an industryleading scanner, and a long-life battery to help mobile workers get more done in less time.

FEATURES & BENEFITS



Purpose-built solution with the right combination of features and reusable accessories for light-duty applications including direct store delivery, pick up and delivery, and retail.



Easy to use, with an intuitive, large touchscreen and a lightweight, comfortable, pocketable design that's still rugged enough for tough field service environments.



Get fast, responsive performance and quick access to critical business information with the snappy Qualcomm Snapdragon 450 octa-core processor.



Built for all-day use, with a removable 4000 mAh lithium-ion battery pack that lasts 12 hours without adding weight or bulk.



Easily capture barcode data, even if damaged, with Honeywell's best-in-class N6603 imager, and document everything with the 13-megapixel auto-focus color camera.

ScanPal EDA51 Technical Specifications

MECHANICAL

Dimension: 157 mm x 78.2 mm x 16.9 mm (6.18 in x 3.08 in x 0.67 in) Weight: 272 g (9.59 oz) Display Size: 12.7 cm (5.0 in) Resolution: 1280 x 720 High Definition Backlight: LED

Touchscreen: Multi-touch capacitive (CTP), GFF

ENVIRONMENTAL Operating Temperature: -10°C to +50°C (+14°F to +122°F)

Storage Temperature: -20°C to +70°C (-4°F to 158°F)

Humidity: 10% to 90% (non-condensing) **Drop:** Multiple 1.2 m (4 ft) drops to concrete at room temperature

Tumble: 300 times at 0.5 m (1.64 ft) **Environmental Sealing:** IP64

SYSTEM ARCHITECTURE

Processor: Qualcomm Snapdragon SDM450, 1.8 GHz octa-core

Memory: 2 GB RAM/16 GB Flash Operating System: Android 8

Storage Expansion: MicroSDHC (up to 128 GB) Camera: 13-megapixel color camera

PC Interface: Micro USB 2.0

Battery: Li-Ion, 3.8 V, 4000 mAh, removable Real-Time Clock (RTC): 10 min backup via super-cap Charging Time: 4.5 hours

Battery Runtime: 12 hours

Scan Engine: Honeywell N6600 Slim Imager Engine (1D/2D barcode symbologies)

Battery Status Indicator: red/green/blue Sensors: acceleration sensor, light sensor, and proximity sensor

Localization & Language: Worldwide English

WIRELESS CONNECTIVITY

WLAN: IEEE 802.11 a/b/g/n/ac Security of WLAN: WEP, 802.1x, TKIP, AES, LEAP, PEAPv0, PEAPv1, EAP-M, SCHAPv2, EAP-GTC, EAP-TLS, EAP-TTLS, WPA-PSK, WPA2 Bluetooth: Bluetooth Class 4.2

WWAN Radio*:

- GSM/EDGE: Bands 2, 3, 5, 8
- UMTS/HSPA+: Bands 1, 2, 4, 5, 8, 9, 19
- CDMA 1xRTT/EVDO: BCO, BC1, BC6
- FDD-LTE: Bands 1, 2, 3, 4, 5, 7, 8, 9, 19, 20, 26
- TDD-LTE: Bands 38, 39, 40, 41

NFC: Integrated Near Field Communication GPS Supported Protocols: Simultaneous Receiver Support for GPS, GLONASS, and BeiDou

ACCESSORIES (STANDARD)

USB Communication Cable: Micro USB 2.0 (communicates to PC, supports adapter/USB charging)

USB Wall Adapter: 5 V/2 A

ACCESSORIES (OPTIONAL) Hand Strap

Scan Handle

Home Base: Charges one terminal and one replaceable battery simultaneously Four-Bay Battery Charger: Charges four batteries simultaneously

Four-Bay Terminal Charger: Charges four terminals simultaneously

WARRANTY

One-year factory warranty

* Available outside of the United States



For a complete listing of all compliance approvals and certifications, please visit www. honeywellaidc.com/compliance.

For a complete listing of all supported barcode symbologies, please visit www.honeywellaidc. com/symbologies.

ScanPal is a trademark or registered trademark of Honeywell International Inc. in the United States and/or other countries.

Android is a trademark or registered trademark of Google Inc. in the United States and/or other countries.

Qualcomm and Snapdragon are trademarks or registered trademarks of Qualcomm Incorporated in the United States and/or other countries

Bluetooth is a trademark or registered trademark of Bluetooth SG, Inc. in the United States and/or other countries.

All other trademarks are the property of their respective owners.

For more information

www.honeywellaidc.com

Honeywell Safety and Productivity Solutions

9680 Old Bailes Road Fort Mill, SC 29707 800-582-4263 www.honeywell.com

ScanPal EDA51 Data Sheet | Rev A | 09/18 © 2018 Honeywell International Inc.

